

## PRODUCT-DETAILS

# S203M-Z63

## Miniature Circuit Breaker - S200M - 3P - Z - 63 A



### Algemene informatie

Type	S203M-Z63
Artikelnummer	2CDS273001R0608
EAN	4016779601382
Omschrijving	Miniature Circuit Breaker - S200M - 3P - Z - 63 A
Omschrijving	System pro M compact S200M miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 10 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200M comply with IEC/EN 60898-1 and IEC/EN 609 47-2, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200M to save 50% space.

### Technische specificaties

Normen	CSA 22.2 No. 235 IEC/EN 60947-2 UL 1077
Aantal polen	3
Aantal beveiligde polen	3
Uitschakelkenmerk	Z
Toegekende stroom ( $I_n$ )	63 A
Nominaal bedrijfsvoltage	acc. to IEC 60898-1 400 V AC acc. to IEC 60947-2 440 V AC
Vermogensverlies	15.6 W at Rated Operating Conditions per Pole 5.2 W

Nominaal isolatievoltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 440 V
Operationeel voltage	Minimum 12 V AC Minimum 12 V DC
Toegekende frequentie (f)	50 / 60 Hz
Nominaal kortsluitvermogen (I <sub>cn</sub> )	(230 V AC) 10 kA (400 V AC) 10 kA
Nominaal ultiem kortsluitvermogen (I <sub>cu</sub> )	(230 V AC) 25 kA (400 V AC) 15 kA (440 V AC) 15 kA
Nominaal vermogen kortsluitvermogen (I <sub>cs</sub> )	(133 V AC) 15 kA (230 V AC) 7.5 kA
Energiebeperkende klasse	3
Overspanningscategorie	III
Verontreinigingsgraad	3
Nominale impuls grensvoltage (U <sub>imp</sub> )	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Diëlektrische testspanning	50/60 Hz, 1 min: 2 kV
Materiaal behuizing	Insulation Group II, RAL 7035
Aansturingsmateriaal	Insulation Group II, Black, Sealable
Aansturingsmarkering	I / O
Onderbreking	Red ON / Green OFF
Beschermingsgraad	IP20 Enclosure with Cover IP40 20000 cycle
Terminaltype	Schroef
Type schroefklem	Failsafe Bi-directional Cylinder-lift Terminal
Verbindingscapaciteit	Busbar 10 / 10 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 25 mm <sup>2</sup> Flexible 0.75 ... 25 mm <sup>2</sup> Rigid 0.75 ... 35 mm <sup>2</sup> Stranded 0.75 ... 35 mm <sup>2</sup>
Aanhaalmoment	2.8 N·m
Aanbevolen schroevendraaier	Pozidriv 2
Montage op DIN-rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Plaats van inbouw	Any
Inbouwdiepte (t <sub>2</sub> )	69 mm
Installatiegrootte	acc. to DIN 43880 1
Aansluiting voeding	Arbitrary

## Milieu

Omgevingsluchttemperatuur	Operation -25 ... +55 °C Storage -40 ... +70 °C
Referentie omgevingsluchttemperatuur	30 °C
Schokweerstand volgens IEC 60068-2-27	25g / 2 shocks / 13 ms
Weerstand tegen trillingen volgens IEC 60068-2-6	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Milieu-omstandigheden	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
RoHS-status	Following EU Directive 2011/65/EU

## Technische specificaties UL/CSA

Maximale bedrijfsspanning UL/CSA	125 V DC 480Y / 277 V AC
Verbindingscapaciteit UL/CSA	Busbar 14-8 AWG Conductor 14-4 AWG
Aanhaalmoment UL/CSA	18 in-lb
Onderbrekende classificatie volgens UL1077	(125 V DC) 10 kA (277 V AC) 6 kA (480Y / 277 V AC) 6 kA

## Afmetingen

Product netto breedte	52.5 mm
Product netto diepte	69 mm
Product netto hoogte	88 mm
Product netto gewicht	0.375 kg

## Verpakkingsinformatie

Pakketniveau 1 Units	carton 1 stuk
Pakketniveau 1 Breedte	92 mm
Pakketniveau 1 Lengte	58 mm
Pakketniveau 1 Hoogte	80 mm
Pakketniveau 1 Brutogewicht	0.4 kg
Pakketniveau 1 EAN	4016779604277
Pakketniveau 2 Units	carton 36 stuk
Pakketniveau 2 Breedte	275 mm
Pakketniveau 2 Lengte	400 mm
Pakketniveau 2 Hoogte	210 mm
Pakketniveau 2 Brutogewicht	13.9 kg
Pakketniveau 2 EAN	4016779978620

## Bestelinformatie

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85362010

## Certificaten en verklaringen (documentnummer)

Conformiteitsverklaring - CE	2CDK403001D0607
Milieu-informatie	2CDK400030D0201
Instructies en handleidingen	2CDS207104P0001
RoHS-informatie	2CDK400003K0203

## Populaire downloads

Gegevensblad, technische informatie	9AKK107046A0423
Instructies en handleidingen	2CDS207104P0001

## Classificatie

Object classificatiecode	F
ETIM 6	EC000042 - Installatieautomaat
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
eClass	V11.0 : 27141901
UNSPSC	39121614

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200922R0001	S2C-S/H6R - Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200912R0001	S2C-H6R - Auxiliary Contact	S2C-H6R	1	piece
2CDS200936R0001	S2C-H11L - Auxiliary Contact	S2C-H11L	1	piece
2CDS200936R0002	S2C-H20L - Auxiliary Contact	S2C-H20L	1	piece
2CDS200936R0003	S2C-H02L - Auxiliary Contact	S2C-H02L	1	piece
2CDS200946R0001	S2C-H6-11R - Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R - Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R - Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200909R0001	S2C-A1 - Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 - Shunt Trip	S2C-A2	1	piece
2CSS200911R0001	S2C-UA 12 DC - Undervoltage release	S2C-UA 12 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC - Undervoltage release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC - Undervoltage release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC - Undervoltage release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC - Undervoltage release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC - Undervoltage release	S2C-UA 400 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC - Undervoltage release	S2C-UA 24 DC	1	piece
2CSS200911R0008	S2C-UA 48 DC - Undervoltage release	S2C-UA 48 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC - Undervoltage release	S2C-UA 110 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC - Undervoltage release	S2C-UA 230 DC	1	piece
2CSS201997R0013	S2C-CM1 - Motor operating device	S2C-CM1	1	piece
2CSS203997R0013	S2C-CM2/3 - Motor operating device	S2C-CM2/3	1	piece
2CSS204997R0013	S2C-CM4 - Motor operating device	S2C-CM4	1	piece
GHS2001901R0003	S2C-DH - Mechanical Accessories	S2C-DH	1	piece
2CSS200998R0001	S2C-BP - Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	S2C-EST - Plug-in base	S2C-EST	1	piece
2CDS200918R0001	S2C-NT - Hand Operated Neutral	S2C-NT	1	piece
2CCA880100R0001	CMS-100PS Sensor	CMS-100PS	1	piece
2CCA880101R0001	CMS-101PS Sensor	CMS-101PS	1	piece
2CCA880102R0001	CMS-102PS Sensor	CMS-102PS	1	piece

## Categorieën

Laagspanningsproducten en -systemen → Modulaire DIN rail producten → Installatieautomaten MCB's

