

PRODUCT-DETAILS

UK660N4

UK660N4 Consumer unit



Algemene informatie

| | |
|---------------|---|
| Type | UK660N4 |
| Artikelnummer | 2CPX031373R9999 |
| EAN | 4011617313731 |
| Omschrijving | UK660N4 Consumer unit |
| Omschrijving | Consumer unit, series UK600, Expansion option: Lateral and bottom, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 7, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, Powder-coated, in RAL 9016, enclosure out of thermoplast, with trim frame and metal door, door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 872 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 872 x 384 x 9, 5-rows, Space units 60, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, with N/PE Quick-terminal, cable fastening rail integrated, assembled with device carrier, device support removable |

Technical

| | |
|-----------------------------|-----------------------|
| Normen | DIN 43871 |
| Nominaal bedrijfsvoltage | Maximum 400 V |
| Operationeel voltage | 400 V |
| Toegekende stroom (I_n) | 63 A |
| Vermogensverlies | $\Delta t = 30K 69 W$ |
| Aantal rijen | 5 |

| | |
|------------------------|-------------------------------|
| Type sluiting | Push Button |
| Configuratietype | assembled with device carrier |
| Afdekplaattype | Door |
| Behuizingstype | Consumer unit |
| Montagetype | Flush-mounted |
| Deurtype | Enkel |
| Uitvoering oppervlakte | Powder-coated |
| Materiaal behuizing | Plastic |
| Afdekstijl | Closed |
| DIN-plaatseenheden | 60 |
| RAL-nummer | RAL 9016 - Verkeerswit |
| Kleur | Traffic white |
| Terminaltype | Quick-Terminal |
| Dikte | " |

Environmental

| | |
|--------------------|--|
| Beschermingsgraad | IP30 |
| Beschermingsklasse | Geïsoleerd |
| RoHS-status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Dimensions

| | |
|--------------------------------|----------|
| Breedte in module-eenheden | 12 |
| Product netto breedte | 384 mm |
| Product netto hoogte | 872 mm |
| Product netto diepte | 97 mm |
| Product netto gewicht | 5.869 kg |
| Inbouwdiepte (t ₂) | 75 mm |

Container Information

| | |
|-----------------------------|-----------------------|
| Pakketniveau 1 Units | pack 1 stuk |
| Pakketniveau 1 Breedte | 390 mm |
| Pakketniveau 1 Hoogte | 880 mm |
| Pakketniveau 1 Lengte | 115 mm |
| Pakketniveau 1 Brutogewicht | 6.104 kg |
| Pakketniveau 1 EAN | 4011617313731 |
| Pakketniveau 2 Units | pallet (lift) 30 stuk |
| Pakketniveau 2 Breedte | 800 mm |
| Pakketniveau 2 Hoogte | 1820 mm |
| Pakketniveau 2 Lengte | 1200 mm |
| Pakketniveau 2 Brutogewicht | 196.07 kg |

Ordering

| | |
|----------------------------|----------|
| Minimale bestelhoeveelheid | 1 stuk |
| Nummer douanetarief | 85381000 |

| | |
|-------------------|--------------|
| E-Number (Sweden) | 2201244 |
| Land van herkomst | Germany (DE) |

Certificates and Declarations (Document Number)

| | |
|------------------------------|-----------------|
| Conformiteitsverklaring - CE | 9AKK107992A8137 |
| Instructies en handleidingen | 2CPC129380M5601 |
| REACH-verklaring | 2CPC100005X0201 |
| RoHS-informatie | 9AKK107992A8137 |

Popular Downloads

| | |
|-------------------------------------|------------------------------------|
| Gegevensblad, technische informatie | 2CPC000001C0101 2CPC000002C0101 |
| Instructies en handleidingen | 2CPC129380M5601 |
| Dimensiediagram | 2CPC000002D0201 |

Classifications

| | |
|--------------------------|---|
| ETIM 7 | EC000214 - Small distribution board |
| ETIM 8 | EC000214 - Small distribution board |
| EPLAN-catalogus boom | Mechanics / Housings / General |
| WEEE-categorie | 4. Large Equipment (Any External Dimension More Than 50 cm) |
| AEEA B2C / B2B | Business To Consumer |
| CN8 | 85381000 |
| eClass | V11.0 : 27142409 |
| Object classificatiecode | U |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|---|--------|----------|-----------------|
| 2CPX031434R9999 | UZ91P4 Enclosure accessories | UZ91P4 | 1 | piece |
| 2CPX062745R9999 | ZK50BT Terminals | ZK50BT | 1 | piece |
| 2CPX030892R9999 | ZK507 Terminals | ZK507 | 1 | piece |
| 2CPX031413R9999 | UZT4 Enclosure accessories | UZT4 | 1 | piece |
| 2CPX031412R9999 | UZT3 Enclosure accessories | UZT3 | 1 | piece |
| 2CPX031787R9999 | UZ641D Enclosure accessories | UZ641D | 1 | piece |
| 2CPX031786R9999 | UZ640D Enclosure accessories | UZ640D | 1 | piece |
| 2CPX031406R9999 | AP660 Enclosure accessories | AP660 | 1 | piece |
| 2CPX061178R9999 | ZX29 ZX Interior fitting system, 62 mm x 125 mm x 68 mm | ZX29 | 1 | piece |
| 2CPX061177R9999 | ZE225 ZE Customized electrical components, 50 mm x 102 mm x 63 mm | ZE225 | 1 | piece |
| 2CPX031408R9999 | UZB2 Enclosure accessories | UZB2 | 1 | piece |
| 2CPX061211R9999 | ZE227 ZE Customized electrical components, 63 mm x 213 mm x 58 mm | ZE227 | 1 | piece |
| 2CPX031788R9999 | UZ642D Enclosure accessories | UZ642D | 1 | piece |
| 2CPX031789R9999 | UZ643D Enclosure accessories | UZ643D | 1 | piece |
| 2CPX031427R9999 | ZE224 ZE Customized electrical components, 54 mm x 50 mm x 58 mm | ZE224 | 1 | piece |
| 2CPX031409R9999 | UZB3 Enclosure accessories | UZB3 | 1 | piece |

Categorieën

Laagspanningsproducten en -systemen → Verdelers → Installatiekasten (System pro E comfort) → Installatiekasten → UK600

