


## PRODUCT-DETAILS

# DS202 AC-C20/0,03

## DS202 AC-C20/0,03 - RCB0



### Algemene informatie

Type	DS202 AC-C20/0,03
Artikelnummer	2CSR252001R1204
EAN	8012542869900
Omschrijving	DS202 AC-C20/0,03 - RCB0
Omschrijving	The RCB0s DS200 series has the function to protect against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts.

### Technische specificaties

Normen	IEC/EN 60947-2 IEC/EN 61009-1
Bedieningskenmerk	Instantaneous
Type reststroom	AC type
Aantal polen	2
Aantal beveiligde polen	2
Toegekende stroom ( $I_n$ )	20 A
Nominale resterende stroom	30 mA
Toegekende spanning ( $U_r$ )	230 V AC
Toegekende frequentie (f)	50/60 Hz
Nominaal kortsluitvermogen ( $I_{cn}$ )	6 kA

Nominaal ultiem kortsluitvermogen ( $I_{cu}$ )	(400 V AC) 10 kA
Uitschakelkenmerk	C
Elektrisch uithoudingsvermogen	10000 cycle
Verbindingscapaciteit	Busbar 10 mm <sup>2</sup> Rigid 25 ... 25 mm <sup>2</sup> Flexible 25 ... 25 mm <sup>2</sup>
Aansluiting voeding	Arbitrary
Positie van neutrale klemmen	Right
Vermogensverlies	6.4 W

## Milieu

Omgevingsluchttempera tuur	Operation -25 ... +55 °C Storage -40 ... +70 °C
-------------------------------	--

## Afmetingen

Product netto breedte	70 mm
Product netto hoogte	0.093 m
Product netto diepte	69 mm
Product netto gewicht	0.440 kg

## Verpakkingsinformatie

Pakketniveau 1 Units	box 1 stuk
Pakketniveau 1 Breedte	80 mm
Pakketniveau 1 Hoogte	105 mm
Pakketniveau 1 Lengte	80 mm
Pakketniveau 1 Brutogewicht	0.48 kg
Pakketniveau 1 EAN	8012542869917

## Bestelinformatie

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85363030

## Certificaten en verklaringen (documentnummer)

Conformiteitsverklaring - CE	9AKK106713A5607
Milieu-informatie	Refer to RoHS
Instructies en handleidingen	9AKK107045A1451
RoHS-informatie	2CSC423002K2701

## Populaire downloads

Gegevensblad, technische informatie	9AKK107991A8329
Instructies en handleidingen	9AKK107045A1451

## Classificatie

Object classificatiecode	F
ETIM 4	EC002281 - Distributor assembly with combination RCCB/MCB
ETIM 5	EC002281 - Distributor assembly with combination RCCB/MCB
ETIM 6	EC002281 - Inbouwunit met aardlekautomaten
ETIM 7	EC002281 - Distributor assembly with combination RCCB/MCB

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200909R0001	S2C-A1 - Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 - Shunt Trip	S2C-A2	1	piece
2CDS200912R0001	S2C-H6R - Auxiliary Contact	S2C-H6R	1	piece
2CDS200922R0001	S2C-S/H6R - Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200946R0001	S2C-H6-11R - Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R - Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R - Auxiliary Contact	S2C-H6-02R	1	piece
2CSS200911R0002	S2C-UA 24 AC - Undervoltage release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC - Undervoltage release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC - Undervoltage release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC - Undervoltage release	S2C-UA 230 AC	1	piece
2CSS200998R0001	S2C-BP - Mechanical tripping device	S2C-BP	1	piece

## Categorieën

Laagspanningsproducten en -systemen → Modulaire DIN rail producten → Aardlekschakelaars RCD's → Aardlekschakelaars met bescherming tegen overbelasting, RCBO

