

PRODUCT-DETAILS

22LF06

INSUL PRC FEM DISCON CU 16-12 AWG



Algemene informatie

Type	22LF06
Artikelnummer	7TAI029020R0018
EAN	5414363112075
Omschrijving	INSUL PRC FEM DISCON CU 16-12 AWG
Omschrijving	Insulation Piercing Magnet Wire Female Disconnect, Length .91 Inches, Width .25 Inches, Length of Teeth .45 Inches, Width of Teeth .25 Inches, Tab Size .250 x .032, Wire Range #16 AWG - #12 AWG 2,580 Circular Mil Area - 12,330 Circular Mil Area, Copper Alloy, Tin Plated

Ordering

EAN	5414363112075
UPC	786210818658
Land van herkomst	United States (US)
Verkoopenheid van maat	each

Container Information

Pakketniveau 1 Units	1000 stuk
Pakketniveau 1 Breedte	4.5 in 114 mm
Pakketniveau 1 Hoogte	3 in

	76 mm
Pakketniveau 1 Lengte	6 in
	152 mm
Pakketniveau 2 Units	5000 stuk
Pakketniveau 2 Breedte	9.7 in
	246 mm
Pakketniveau 2 Hoogte	6.8 in
	173 mm
Pakketniveau 2 Lengte	16 in
	406 mm

Additional Information

Toepassing	For aluminum to copper, aluminum to aluminum or copper to copper magnet wire connections.
Merk / Label	Sta-Kon
Ingangsdatum	19801202
Materiaal	Copper
Productnaam	ELECTRICAL TERMINAL
Producttype	Vinyl Insulated Female Disconnect
Speciale functies	Designed to penetrate magnet wire insulation during application, eliminating the need for stripping, brazing, welding or other methods of joining magnet wire.
Normen	UL E9809
Sub Brand / Label	Dragon Tooth
Uitvoering oppervlakte	Tin Plated

Certificates and Declarations (Document Number)

Gegevensblad, technische informatie	22LF06
Instructies en handleidingen	22LF06

Classifications

ETIM 6	EC001059 - Perskoppelstuk voor koperkabel
ETIM 7	EC001059 - Crimp splices for copper conductor
ETIM 8	EC001059 - Crimp splices for copper conductor
UNSPSC	39121447
WEEE-categorie	Product Not in WEEE Scope
IGCC (IDEA granulaire categoriecode)	4667 >> Wire terminal disconnect

Categorieën

Laagspanningsproducten en -systemen → Installatietechniek producten → Draad- en kabelmanagement → Compressie- en mechanische aansluitingen

