


## BCO MOD ML2 BD EX 24 (927 084)


- LifeCheck arrester monitoring and integrated status indication
- Two-pole protection module for optimal protection of one pair in intrinsically safe signal circuits
- For installation in conformity with the lightning protection zone concept at the boundaries from  $0_A -2$  and higher



Figure without obligation



Basic circuit diagram BCO MOD ML2 EX 24



Dimension drawing BCO MOD ML2 EX 24

Protection module with a width of 6 mm for BLITZDUCTORconnect combined arresters with status indication for protecting one pair of intrinsically safe measuring circuits and bus systems, meets FISCO requirements. Insulation strength > 500 V line-ground.

| Type  | BCO MOD ML2 BD EX 24  |
|---|---|
| Part No.  | 927 084   |
| SPD class   | TYPE 2 P2   |
| Impulse category  | D1, C1, C2, C3, B2  |
| Nominal voltage ( $U_n$ )   | 24 V  |
| Max. continuous operating voltage (d.c.) ( $U_c$ )  | 36 V  |
| Max. continuous operating voltage (a.c.) ( $U_c$ )  | 25.4 V  |
| Nominal current at 80 °C ( $I_n$ )  | 0.5 A   |
| D1 Total lightning impulse current (10/350 $\mu$ s) ( $I_{imp}$ )                                   | 3 kA  |
| D1 Lightning impulse current (10/350 $\mu$ s) per line ( $I_{imp}$ )                                | 1.5 kA  |
| C2 Total nominal discharge current (8/20 $\mu$ s) ( $I_n$ )   | 10 kA   |
| C2 Nominal discharge current (8/20 $\mu$ s) per line ( $I_n$ )                                      | 5 kA  |
| Voltage protection level line-line for $I_n$ C2 ( $U_p$ )   | $\leq 65$ V   |
| Voltage protection level line-PG for $I_n$ C2 ( $U_p$ )   | $\leq 1100$ V   |
| Voltage protection level line-line for $I_n$ C1 ( $U_p$ )   | $\leq 65$ V   |
| Voltage protection level line-PG for $I_n$ C1 ( $U_p$ )   | $\leq 1100$ V   |
| Voltage protection level line-line at 1 kV/ $\mu$ s C3 ( $U_p$ )                                    | $\leq 48$ V   |
| Voltage protection level line-PG at 1 kV/ $\mu$ s C3 ( $U_p$ )                                      | $\leq 1000$ V   |
| Series resistance per line  | 1 ohm(s)  |
| Cut-off frequency line-line ( $f_c$ )   | 3.5 MHz   |
| Operating temperature range ( $T_U$ )   | -40 °C ... +80 °C   |
| Operating state / fault indication  | green / red   |
| Degree of protection (with plugged-in protection module)  | IP 20   |
| Plugs into  | BCO Ex base part  |
| Earthing via  | BCO Ex base part  |
| Enclosure material  | polyamide PA 6.6  |
| Colour  | blue  |
| Test standards  | IEC 61643-21 / EN 61643-21                                  |
| Approvals   | SIL, ATEX, IECEx  |
| ATEX approvals (1) (in preparation)   | TUR XX ATEX XXXX.X: II 2(1)G Ex ia [ia Ga] IIC T4 ... T6 Gb |
| ATEX approvals (2) (in preparation)   | TUR XX ATEX XXXX.X: II 2G Ex ib IIC T4 ... T6 Gb            |
| ATEX approvals (3) (in preparation)   | TUR XX ATEX XXXX.X: II (1)D [Ex ia Da] IIIC                 |
| IECEx approvals (1) (in preparation)  | IECEx TUR XX.XXXXX: Ex ia [ia Ga] IIC T4 ... T6 Gb          |
| IECEx approvals (2) (in preparation)  | IECEx TUR XX.XXXXX: Ex ib IIC T4 ... T6 Gb                  |
| IECEx approvals (3) (in preparation)  | IECEx TUR XX.XXXXX: [Ex ia Da] IIIC                         |
| Extended technical data:  | -----   |
| - Max. discharge current (8/20 $\mu$ s) [1/2 - PG], [1+2 - PG] ( $I_{max}$ )                        | 20 kA   |
| - Voltage protection level line-PG at 1 kV/ $\mu$ s C3 after being subjected to $I_{max}$ ( $U_p$ ) | $\leq 1000$ V   |
| Weight  | 14 g  |
| Customs tariff number (Comb. Nomenclature EU)   | 85363010  |
| GTIN  | 4013364410206   |
| PU  | 1 pc(s)   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.