

UK K25 FL30 SQL (773 251)

- Universal clamp, T pin shaft
- T pin according to DIN 48087
- For flat and round conductors up to 30 mm and fixed ball points, ball Ø25 mm



Figure without obligation




Figure without obligation

*) Klemmbereich und Seilquerschnitt für Unniklemmen an:			
Kugelfestpunkt Ø	T-Anschluss Halsweite	Rd / Fl Klemmbereich	Seilquerschnitt
20/25/30 mm	15/18 mm	20/30 mm	16 mm²
20/25/30 mm	15/18 mm	20/30 mm	25 mm²
20/25/30 mm	15/18 mm	20/30 mm	35 mm²
20/25/30 mm	15/18 mm	20/30 mm	50 mm²
20/25/30 mm	15/18 mm	20/30 mm	70 mm²
20/25/30 mm	15/18 mm	-	95 mm²
-/25/30 mm	-	-	120 mm²
-	-	-	150 mm²

Type	UK K25 FL30 SQL
Part No.	773 251
For fixed ball point Ø	25 / 30 mm
Anti-rotation cable lug	PK2 (Ø10.5 mm)
For cable cross section Cu	50 mm²
Max. short-circuit current I _k 0.06 s	34.0 kA
DB drawing No.	4 Ebgw 01.59
DB material No.	157 538
Material (pressure plate)	St/gal Zn
Material (clamp body)	Copper alloy
Material (shaft)	Stainless steel
Weight	901 g
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364005990
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.