

APC 64 66 (785 759)



Figure without obligation

- Reinforced stand-up collar
- Zip and hook-and-loop fasteners

Type	APC 64 66
Part No.	785 759
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W_{arc} or W_{LEP})	320 kJ
EuroTest PIP001 (10 kA / 1 s – three-pole)	Yes
Extended electric arc energy (W_{arc} or W_{LEP}) (based on box test)	630 kJ
Arc Rating – ATPV (Open Arc Test)	33.1 cal / cm ²
PPE category (NFPA 70E)	PPE 3
Size (international)	64 / 66 (3XL)
Outer material	Siliconised calf grain leather, 100% Kevlar interlock knit
Inner material	100% cotton
Material (sewing thread)	100% Kevlar
Standard	IEC 61482-2, EN ISO 14116
Weight	3,28 kg
Customs tariff number (Comb. Nomenclature EU)	42031000
GTIN	4013364329362
PU	1 pc(s)

In case of very heavy soiling, the protective coat can be dry cleaned by a specialist leather cleaner.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.