



NEW APT OD OG 27 (787 865)



Figure without obligation

Type	APT OD OG 27
Part No.	787 865 <small>EN 61482-2</small>
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W_{arc} or W_{LBP})	320 kJ
Arc rating – ATPV (open arc)	16 cal / cm ² *)
Arc rating – ELIM (open arc)	13 cal / cm ²
PPE category (NFPA 70E)	PPE 2
Material	Modacrylic (40%), viscose (59%), static inhibitors (1%), PU membrane: meta-armid knitting (100%)
Weight per unit area	300 g/m ²
Material (sewing thread)	Kevlar (100%)
Standard	IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 20471, EN 13034, EN ISO 13688, EN ISO 11611
Primary colour	fluorescent orange
Secondary colour	grey
Zipper	red
Size (international)	27 (L-K)
Design code	TOORGRRE0000P0
Weight	850 g
Customs tariff number (Comb. Nomenclature EU)	62034911
GTIN	4013364491922
PU	1 pc(s)

*) Outer fabric after preparation

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.