

Compact air-to-water heat pump with 90° air deflection

Max. flow temperature: 60 °C
 Casing colour: White (similar to RAL 9003)
 Brown-red design screen (RAL 3011)

Heat pump for heating purposes for indoor installation with integrated WPM Econ5Plus control. Sound-optimised through the use of slow-running EC 3D radial fan, an encapsulated compressor housing and a free-swinging compressor baseplate for solid-borne sound insulation. High coefficients of performance (COP) thanks to high-performance evaporator, electronic expansion valve and electronic control of the volume flows. Increased system efficiency possible via intelligent room temperature control (Smart RTC). Maximum operational safety via sensor monitoring of the refrigeration circuit with self-optimising defrosting. This enables the downtimes in cycle operation to be used for natural defrosting; integrated thermal energy metering (display of the calculated quantity of thermal energy for heating and domestic hot water preparation on the heat pump manager). The integrated air circuit with 90° air deflection enables installation in a corner without air ducts or wall installation with air ducts on the air outlet side. The control panel is integrated in a design screen and can also be used as wired remote control using the wall mounting set (special accessories MS PGD). Compact design with optional domestic hot water preparation and integrated components for direct connection of an unmixed heating circuit (must not be used for bivalent systems):

- Expansion vessel (24 l)
- High-efficiency heat circulating pump (note the free compression)
- Overflow valve and safety module with pressure gauge
- Buffer tank (50 l) with integrated 2 kW heating element

At an external temperature of -10 °C, the maximum flow temperature that can be achieved is 56 °C. Flow and return sensor integrated; external sensor (standard NTC-2) in the scope of supply. Dirt trap and flow rate switch built in.



Technical data

Dimplex Compact air-to-water heat pump with 90° air deflection (Low temperature)

Order reference	LIK 12TU
Heat pump code	1039
Casing colour	White (similar to RAL 9003)
Max. flow temperature	60 °C
Lower operating limit heat source (heating operation) / Upper operating limit heat source (heating operation)	-22 to 35 °C
Heat output A-7/W35 / COP A-7/W35*	7,1 kW / 3,3
Heat output A2/W35 / COP A2/W35*	9,4 kW / 4,2
Heat output A7/W35 / COP A7/W35*	11,5 kW / 5,0
Heat output A10/W35 / COP A10/W35*	12,00 kW / 5,3
Nominal power consumption according to EN 14511 at A2/W35	2,35 kW
Nominal power consumption according to EN 14511 at A7/W35	2,4 kW
Sound power level	50 dB (A)
Sound pressure level in 1 m	43 dB (A)
Refrigerant / Amount of refrigerant	R410A / 4,6 kg
Max. heating water flow rate / Pressure drop	2,0 m³/h / 39400 Pa
Heat source flow (min.)	4100 m³/h
Dimensions (W x H x D)**	960 x 1950 x 780 mm
Weight	310 kg
Rated voltage	3/N/PE ~400 V, 50 Hz
Starting current	19 A
Fuse protection***	C 10 A
Type of defrosting	Reverse circulation
Connection heating	1 ¼ inch

*Heat output and coefficient of performance (COP) according to EN 14511

**Please note that additional space is required for pipe connections, operation and maintenance.

***Die Absicherung ist als allpolige Trennvorrichtung auszuführen (gemeinsame Abschaltung aller Phasen)!

Description	Order ref.	Article number	Sample item	Item	Price
Heat pumps					
Compact air-to-water heat pump with 90° air deflection	LIK 12TU	372830	1		
Elasticated sound insulation underlay strips	SYL 250	352260	1		
DN 32 double-sphere rubber expansion joint	KOMP 32	362060			
Heat source accessories					
Air duct hose kit for LI 9/12TU and LI 15TE outlet	LUS 9A-2	370120			
Air duct hose kit for air outlet, length 4 m	LUS 9A-4	370130			
90° air duct bend*	LKB 600A	366150			
90° air duct bend*	LKB 800A	366170			
Connection kit	VSLK 600	367680			
Connection kit	VSLK 800	367700			
Connection frame set air duct	ARLK 600	370270			
Connection frame set air duct	ARLK 800	370290			
Sealing collar 600	DMK 600-1	356120			
Sealing collar 800	DMK 800-1	356140			
Deflector hood	LUH 600	358620			
Rain guard for LI	RSG 600	340230	1		
Rain guard for LI(H)	RSG 800	340250	1		
Hydraulic accessories					
Screw-in radiator 4.5 kW 1¼" for LIK 8TES	CEHK 345	366810			
Manifold bar	VTB 25	339870			
Manifold bar (3-fold) for modules DN 25 and DN 32	VTB 32	367770			
Domestic hot water module/unmixed heating circuit module	WWM 25	346600	1		
Mixed heating circuit module with temperature sensor	MMH 25	348640			
Electronically controlled circulating pump with coupling relay	UPH 60-25	367870	1		
Electronically regulated wet running pump (0-10 V) with coupling relay	UPE 70-25	362790			
Electronically regulated wet running pump (0-10 V) with coupling relay	UPE 80-25	362810			
Immersion heater pipe assembly*	HDLR 450	337450			
Heating accessories					
Fan convector heating with EC fan	SRX 080EM	367500			
Fan convector heating with EC fan	SRX 120EM	367510			
Fan convector heating with EC fan	SRX 140EM	367520			
Fan convector heating with EC fan	SRX 180EM	367530			
Fan convectors heating 1400 W	SRX 140M	359100			
DHW preparation accessories					
Domestic hot water cylinder (300l) with temperature sensor	WWSP 332	346610	1		
Flange heater for domestic hot water	FLH 60	338060			
Flange heater for domestic hot water	FLHU 70	338070	1		
Flange heater for domestic hot water	FLH 90	366130			
FLH 25M flange heater	FLH 25M	349430			
Safety valve combination	SVK 852	326660			
Domestic hot water cylinder (400 l) with temperature sensor*	WWSP 442	372840			
Design domestic hot water cylinder with sheet metal coverings and temperature sensor*	WWSP 442E	353370			
Domestic hot water cylinder (500l) with temperature sensor*	WWSP 556	370080			
500 l solar cylinder for heat pump*	WWSP 540 SOL	361090			
Pump unit DN 25 for direct connection of the domestic hot water cylinder	WPG 25	356030	1		
Electronically controlled circulating pump with coupling relay	UPH 60-25	367870	1		
Fresh water station FWS 27	FWS 27	367310			
FWS WT fresh water station	FWS WT	368100			
Control accessories					
Extension for an Ethernet network connection	NWPM	356960			
Extension for a KNX/EIB connection	EWPM	356970			
Remote control for WPM 2006/2007/EconPlus/R*	AP PGD	356570			
Swimming pool/remote fault indicator relay module	RBG WPM	339700			
Thermostat for heating and domestic hot water	KRRV 003	322070			
Outside temperature sensor with casing	FG 3115	336620			

Description	Order ref.	Article number	Sample item	Item	Price
Temperature sensor NTC-10 with metal sleeve	NTC-10M	363600			
Solar thermal systems accessories					
Heat exchanger station SST 25 for solar energy systems up to max. 10 m ²	SST 25	348430			

* Other specific accessories available / required

Important information:

The combination of the components and the quantities indicated represent a non-binding sample system, which needs to be tested and individually adapted as required. Pump dimensioning must be reviewed according to the pressure loss of the system and the minimum heating water flow rate of the heat pump.