






MICRO TUBE 2 ON RECT


| | | |
|-----|-------------------|--|
| REF | A6173W/2OR/927/PD | Micro Tube 2 ON RECT white 927 phase DIM/1-10V |
| | A6173W/2OR/930/PD | Micro Tube 2 ON RECT white 930 phase DIM/1-10V |
| | A6173B/2OR/927/PD | Micro Tube 2 ON RECT black 927 phase DIM/1-10V |
| | A6173B/2OR/930/PD | Micro Tube 2 ON RECT black 930 phase DIM/1-10V |
| | A6173W/2OR/927/D | Micro Tube 2 ON RECT white 927 DALI DIM |
| | A6173W/2OR/930/D | Micro Tube 2 ON RECT white 930 DALI DIM |
| | A6173B/2OR/927/D | Micro Tube 2 ON RECT black 927 DALI DIM |
| | A6173B/2OR/930/D | Micro Tube 2 ON RECT black 930 DALI DIM |


| | |
|---------------|--|
| LED | COB LED |
| LED LM OUTPUT | 2x 630 lm |
| POWER CONS. | 2x 7 W |
| DRIVE CURRENT | 230 Vac built-in driver |
| COLOR TEMP. | 2.700 / 3.000 K |
| CRI | > 90 |
| REFLECTOR | 36° |
| FINISH | white RAL 9016 tex black RAL 9005 tex |
| ADJUSTABLE | 90° x 355° |
| OPTIONAL | C6029W Micro Tube cone white C6029G Micro Tube cone gold C6030 Micro Tube 24° lens veneer finish - see p. 260 |






EG-FPC



ceiling


indoor


class 3


IP20
IP rating


LED


F