ACCESSORIES FOR KEY BLOCK AND ULISSE SERIES



ACCESSORIES for Key Block Series

| Code | Description | Colour | Single package | Internal packing | Packing unit | Mark |
|-------|--|--------|-------------------|------------------|--------------|------|
| 73990 | Wall box for Key Block sockets fitted with screw covers | | Shrink film | - | 10 | C€ |
| 73991 | Wall box for Key Block sockets fitted with wall trame | | Shrink film | - | 6 | C€ |
| 73995 | Spacer to be used as horizontal connection between wall boxes for Key Block sockets | | Bag | - | 6 | C€ |
| 74189 | Blank flange 180x90 mm. suitable for blank ULISSE boards and for part no. 73990 - 73991 | | Bag | - | 12 | C€ |
| 74185 | Drilled flange IP44 dim.90x180 mm. with 8 screws for fixing 2 sockets dim.50x62 mm. | | Bag | - | 12 | C€ |

ACCESSORIES for Ulisse Series

| Code | Description | Colour | Single package | Internal packing | Packing unit | Mark |
|-------|--|--------|-------------------|------------------|-----------------|------|
| 74186 | Drilled flange IP44 dim. 75x85 mm. with 8 screws for fixing 1 socket dim. $50x62$ mm. | | Bag | - | 20 | C€ |
| 74187 | Blank flange 75x85 mm. | | Bag | - | 20 | C€ |
| 73989 | Fixing device for sockets for industrial/domestic appliances with flange 50x62 mm. and 90x100 mm. | | Bag | - | 5 | |
| 73987 | Kit of 4 galvanized TSP self-tapping screws Ø3x20 mm. for sockets for domestic/industrial appliances with flange 50x62 mm. | | Bag | - | 20 | |

Industrial and civil flush-mounted socket Argo serie reduced flange 50x62 mm - IP44 (see schedule at page 64)

| Code | Description | Rated Current | Poles | Earth Position | Rated Operating Voltage | Colour | Single package | Internal packing | Packing unit |
|-------|---|------------------|--------|-------------------|----------------------------|--------|-------------------|---------------------|-----------------|
| 71085 | Industrial Sockets | 16A | ■ 2P+E | 6h | 200-250V | | Вох | - | 5 |
| 71087 | Industrial Sockets | 16A | ■ 2P+E | 6h | 200-250V | | Вох | - | 5 |
| 71093 | Flush-mounting socket italian/german std. | 16A | ■ 2P+E | | 200-250V | | Вох | - | 5 |
| 71094 | Flush-mounting socket french std. | 16A | ■ 2P+E | | 200-250V | | Bag | - | 20 |

Angled flush-mounted socket Argo serie flange 75x85 mm - IP67 (see schedule at page 64)

| Code | Rated Current | Poles | Earth Position | Rated Operating Voltage | Colour | Single package | Internal packing | Packing unit |
|-------|------------------|----------|-------------------|----------------------------|--------|-------------------|---------------------|-----------------|
| 71650 | 16A | ■ 2P+E | 6h | 200-250V | | Вох | - | 5 |
| 71654 | 16A | ■ 3P+E | 6h | 380-415 V | | Вох | - | 5 |
| 71655 | 16A | ■ 3P+N+E | 6h | 380-415 V | | Box | - | 5 |

