


Toestelcontactstop - Bestelnr. 391



■ schroefklemmen

Technische informatie

| | |
|-------------------|----------------|
| Ampere | 32 A |
| Polen | 5 p |
| Voltage | 400 V |
| Uurstand | 6 h |
| Hertz | 50-60 Hz |
| Aansluittechniek | schroefklemmen |
| Contacten | standaard |
| Beschermingsgraad | IP 44 |



| Tekening 2 MB 73 | Amp. Polen | 16 | | 32 | | |
|---------------------------------|---------------|------|------|-----|-----|-----|
| | | 4 | 5 | 3 | 4 | 5 |
| Maten in mm | a | 85 | 85 | 75 | 75 | 75 |
| | b | 85 | 85 | 90 | 90 | 90 |
| | c | 75 | 79 | 87 | 87 | 90 |
| | d | 64 | 64 | 45 | 45 | 45 |
| | d1 | 10 | 10 | 13 | 13 | 13 |
| | e | 64 | 64 | 78 | 78 | 78 |
| | f | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| | g | 6 | 6 | 6 | 6 | 6 |
| | g.1 | 2 | 2 | 2 | 2 | 2 |
| | h | 129 | 129 | 137 | 137 | 138 |
| Kabelaansluiting van/tot mm² | i | 50 | 50 | 55 | 55 | 55 |
| | | 1 | 1 | 2,5 | 2,5 | 2,5 |
| | | -2,5 | -2,5 | -6 | -6 | -6 |