



## BE GY16 E VU 5G1,5 Std R0,25

Preflex 16 mm+H07V-U Eca 5G1.5 G/Y BL BR BLA GR C25

### Properties of the article

◦ Articulenumber	1234000340
◦ Barcode	5420056251723
◦ Category	Energy & Light
◦ Gross weight (kg)	3.7
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	25

### Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Grey
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

### Characteristics of the cable or cable combination

◦ Cable type	H07V-U 5G1.5
◦ Color	
◦ Insulation	PVC
◦ CPR Class	eca

### Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	IEC 60227-1; EN 50575:2014+A1:2016

### Certificates

