



BE GY25 E VU 4G4 GGBLBRZ R0,5

Preflex 25mm+H07V-U Eca 4G4 G/Y BL BR BLA C50

Properties of the article

| | |
|----------------------|--------------------|
| ◦ Articlenumber | 1234000441 |
| ◦ Barcode | 5420056257442 |
| ◦ Category | Energy & Light |
| ◦ Gross weight (kg) | 13.4 |
| ◦ Dimensions (WxLxH) | 500 x 500 x 200 MM |
| ◦ Packaging | Roll |
| ◦ Length | 50 |

Properties of the Preflex[®] tube

| | |
|---------------------------------|----------------------------|
| ◦ Material of tube | Halogen-free Polypropylene |
| ◦ Color | Grey |
| ◦ Outer diameter (mm) | 25 |
| ◦ Inner diameter (mm) | 18.3 |
| ◦ Classification | ICTA 3422 |
| ◦ Pressure resistance | 750N / 23°C |
| ◦ Impact resistance | 6J / -5°C |
| ◦ Breakthrough test | 2000V / 50-60 Hz 15min. |
| ◦ Insulation resistance | min. 100 Mohm/80cm |
| ◦ Test temperature | -5°C tot +90°C |
| ◦ Min. installation temperature | -5°C |

Characteristics of the cable or cable combination

| | |
|--------------|---|
| ◦ Cable type | H07V-U 4G4 |
| ◦ Color |  |
| ◦ Insulation | |
| ◦ CPR Class | eca |

Certificates

- Norm van de buis
- Norm van de kabel

Certificates

