



## BE GY20 C XVB 5G1,5 R0,5

Preflex 20mm+XVB Cca (a3d2s3) 5G1.5 C50

### Properties of the article

◦ Articlenumber	1234000447
◦ Barcode	5420056256131
◦ Category	Energy & Light
◦ Gross weight (kg)	10.8
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	50

### Properties of the Preflex<sup>®</sup> tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Grey
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

### Characteristics of the cable or cable combination

◦ Cable type	XVB 5G1.5
◦ Color	
◦ Insulation	
◦ CPR Class	cca s3 d2 a3

### Certificates

- Norm van de buis
- Norm van de kabel

### Certificates

