



BE GY25 C XVB 5G4 R0,5

Preflex 25mm+XVB Cca (a3d2s3) 5G4 C50

Properties of the article

◦ Articlenumber	1234001065
◦ Barcode	5420056256261
◦ Category	Energy & Light
◦ Gross weight (kg)	19.2
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	50

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Grey
◦ Outer diameter (mm)	25
◦ Inner diameter (mm)	18.3
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	XVB 5G4
	
◦ Color	
◦ Insulation	PVC
◦ CPR Class	cca s3 d2 a3

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 50575

Certificates

