



## BE GY20 C TPVF 6x2x0,6 R1

Preflex 20mm+TPVF Cca (a3d2s3) 6x2x0.6  
C100

### Properties of the article

◦ Articulenumber	1234001102
◦ Barcode	5420056259804
◦ Category	Communication
◦ Gross weight (kg)	15.2
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

### Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Grey
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

### Characteristics of the cable or cable combination

◦ Cable type	TPVF 6x2x0.6
◦ Color	
◦ Insulation	
◦ CPR Class	cca s3 d2 a3

### Certificates

- Norm van de buis
- Norm van de kabel

### Certificates

