



## BE BL20 E FTP6 H3

Preflex 20mm+F/UTP CAT6 Eca D 300

### Properties of the article

|                      |                    |
|----------------------|--------------------|
| ◦ Articulenumber     | 1234001299         |
| ◦ Barcode            | 5420056266536      |
| ◦ Category           | Data               |
| ◦ Gross weight (kg)  | 35.4               |
| ◦ Dimensions (WxLxH) | 500 x 500 x 200 MM |
| ◦ Packaging          | Reel Ø 80 cm       |
| ◦ Length             | 300                |

### Properties of the Preflex<sup>®</sup> tube

|                                 |                            |
|---------------------------------|----------------------------|
| ◦ Material of tube              | Halogen-free Polypropylene |
| ◦ Color                         | Blue                       |
| ◦ Outer diameter (mm)           | 20                         |
| ◦ Inner diameter (mm)           | 14.1                       |
| ◦ Classification                | ICTA 3422                  |
| ◦ Pressure resistance           | 750N / 23°C                |
| ◦ Impact resistance             | 6J / -5°C                  |
| ◦ Breakthrough test             | 2000V / 50-60 Hz 15min.    |
| ◦ Insulation resistance         | min. 100 Mohm/80cm         |
| ◦ Test temperature              | -5°C tot +90°C             |
| ◦ Min. installation temperature | -5°C                       |

### Characteristics of the cable or cable combination

|              |             |
|--------------|-------------|
| ◦ Cable type | F/UTP CAT 6 |
| ◦ Color      |             |
| ◦ Insulation |             |
| ◦ CPR Class  | eca         |

### Certificates

- Norm van de buis
- Norm van de kabel

### Certificates

