



BE LGN16 LS FIRE-SNA 3x1,5 R1

Preflex SAFE 16mm+Brandvrij Rf 1h30 3x1,5 LS0H
R100

Properties of the article

◦ Articlenumber	1234000034
◦ Barcode	5420056245166
◦ Category	Fire
◦ Gross weight (kg)	15.8
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	FIRE SNA 3x1.5
◦ Color	
◦ Insulation	
◦ CPR Class	

Certificates

◦ Norm van de buis	
◦ Norm van de kabel	SD / En 61034-1

Certificates

