



## BE LGN16 LS FIRE-TEL 1P0,9 R1

Preflex SAFE 16mm+PYRO-TEL (LS0H) Rf 1h 1P0.9 R100

### Properties of the article

◦ Articulenumber	1234000080
◦ Barcode	5420056210911
◦ Category	Fire
◦ Gross weight (kg)	12.8
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

### Properties of the Preflex<sup>®</sup> tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

### Characteristics of the cable or cable combination

◦ Cable type	FIRE TEL 1P0.9
◦ Color	
◦ Insulation	LS0H
◦ CPR Class	

### Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	NBN 713 020 ; EN 61034 1 ; EN 50267 2 3 ; EN 60332 3 24 ; EN 60216 ; UV: EN50289-4-17

### Certificates

