



BE LGN20 LS C UTP6+MDIC H2,5

Preflex SAFE 20mm+ U/UTP 6 LSOH+ Proximus MDIC D 250

Properties of the article

◦ Articulenumber	1234000159
◦ Barcode	5420056243551
◦ Category	Fibre Optic
◦ Gross weight (kg)	31.0
◦ Dimensions (WxLxH)	500 X 500 X 200 MM
◦ Packaging	Reel Ø 80 cm
◦ Length	250

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

	U/UTP LSOH	
	CAT6	FO Proximus
◦ Cable type		
◦ Color		
◦ Insulation		
◦ CPR Class	cca s1 d1 a1	

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	

Certificates

