



BE LGN40 TD R0,25

Preflex SAFE 40mm+ with pull wire C 25

Properties of the article

| | |
|----------------------|--------------------|
| ◦ Articlenumber | 1234000293 |
| ◦ Barcode | 5420056245241 |
| ◦ Category | Empty |
| ◦ Gross weight (kg) | 5.7 |
| ◦ Dimensions (WxLxH) | 500 x 500 x 200 MM |
| ◦ Packaging | Roll |
| ◦ Length | 25 |

Properties of the Preflex[®] tube

| | |
|---------------------------------|----------------------------|
| ◦ Material of tube | Halogen-free Polypropylene |
| ◦ Color | Light Green |
| ◦ Outer diameter (mm) | 40 |
| ◦ Inner diameter (mm) | 30.0 |
| ◦ Classification | ICTA 3422 |
| ◦ Pressure resistance | 750N / 23°C |
| ◦ Impact resistance | 6J / -5°C |
| ◦ Breakthrough test | 2000V / 50-60 Hz 15min. |
| ◦ Insulation resistance | min. 100 Mohm/80cm |
| ◦ Test temperature | -5°C tot +90°C |
| ◦ Min. installation temperature | -5°C |

Characteristics of the cable or cable combination

| | |
|--------------|-----------|
| ◦ Cable type | Trekdraad |
| ◦ Color | |
| ◦ Insulation | |
| ◦ CPR Class | |

Certificates

| | |
|---------------------|---|
| ◦ Norm van de buis | EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2 |
| ◦ Norm van de kabel | |

Certificates

