



BE LGN20 LS C Z1U 9G1,5 Std+ZRZWWOR R1

Preflex SAFE 20mm+H07Z1-U Cca (a1d1s1) 9G1,5 C100

Properties of the article

◦ Articulenumber	1234000618
◦ Barcode	5420056254144
◦ Category	Energy & Light
◦ Gross weight (kg)	24.6
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	H07Z1-U 9G1.5
◦ Color	
◦ Insulation	
◦ CPR Class	cca s1 d1 a1

Certificates

- Norm van de buis
- Norm van de kabel

Certificates

