



BE LGN16 LS C UFTP6A H5

Preflex SAFE 16mm+F/UTP LS0H Cca (a1d2s1) CAT6-A D500

Properties of the article

◦ Articulenumber	1234001228
◦ Barcode	5420056257145
◦ Category	Data
◦ Gross weight (kg)	49.0
◦ Dimensions (WxLxH)	500 X 500 X 200 MM
◦ Packaging	Reel Ø 80 cm
◦ Length	500

Properties of the Preflex[®] tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	U/FTP CAT6-A
◦ Color	
◦ Insulation	
◦ CPR Class	cca s1 d1 a1

Certificates

- Norm van de buis
- Norm van de kabel

Certificates

