



BE LGN16 LS C FUTP6A R1

Preflex SAFE 16mm+ F/UTP LS0H Dca CAT6-A C100

Properties of the article

◦ Articulenumber	1234001229
◦ Barcode	5420056268639
◦ Category	Data
◦ Gross weight (kg)	10.1
◦ Dimensions (WxLxH)	500 X 500 X 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	16
◦ Inner diameter (mm)	10.6
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	F/UTP CAT6-A
◦ Color	
◦ Insulation	LS0H
◦ CPR Class	b2ca s1 d1 a1

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	ISO/IEC 11801-1:2017 (Ed. 1.0) / ISO/IEC 11801-2:2017 (Ed. 1.0) ; IEC 61156-5:2012 (Ed. 2.1) ; EN 50173-1:2011 ; EN 50173-2:2007 including amendment A1:2010 ; EN 50288-11-1:2012 ; ANSI/TIA-568-C.2:2009

Certificates

