



> 100 dB <
> 16 TONES <
> 2 LEVELS OF ALARM <



CAN BE INSTALLED WITH



See Base Section on page 28

	SHALLOW	DEEP	WALL
12/24V ACDC	✓	✓	✓
PNP 12/24V DC	✗	✗	✓
40/80V ACDC	✗	✓	✓
120/240V AC	✗	✓	✓
JR 120/240V AC	✗	✗	✓
	FLUSH	DOUBLE	POLE

CERTIFICATIONS



SIR-E JUNIOR | PART NO

	90417	90418	90420	90419
EURO	90387	90390	90389	90388
APAC				

SIR-E JUNIOR

Multifunctional electronic sounder developed with a multichannel technology that allows two separate levels of alarm (pre-alarm, alarm) controllable via independent electric contacts. SIR-E JUNIOR benefits from 16 different tones over two channels (selectable via dip-switch).

European (EURO) and Asia Pacific (APAC) tones available.

TECHNICAL SPECIFICATIONS

MULTIFUNCTION

2 levels of alarm (pre-alarm, alarm) controllable via independent electric contacts

HIGH ACOUSTIC PERFORMANCE

CHANNEL 1 | PRE-ALARM

A powerful up to 100 dB electronic tone, ideal for alerting staff of a danger or a serious change of operating circumstances (tone selectable via dip switch "A" out of 8 tones)

CHANNEL 2 | ALARM

A powerful up to 100 dB electronic tone, ideal for alerting staff of a permanent change of operating circumstances (tone selectable via dip switch "B" out of 8 tones)

MULTITONE

16 tones available, including fire alarm, industrial and civil tones

VOLTAGES

According to the installed base

PROTECTION GRADE

IP65, UL TYPE 3R, suitable for outdoor applications

OPERATING TEMPERATURE

-30/+50 °C

MECHANICAL FEATURES

Self extinguishing PC body with high impact resistance, suitable for outdoor applications thanks to the IP65/TYPER 3R protection grade

ACOUSTIC FEATURES

High performance electromagnetic buzzer

DRAWINGS, DIMENSIONS AND WEIGHTS

