


PIXO LINE 1500 UGR19 830 BLACK

Artikelnummer 0007827




PRO




Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Aluminium body, plastic end caps,aluminised plastic low glare optics in a single line configuration, light beam angle:70° Textured black finishing colour. Light color temperature: 3000K, warm white, max. system power: 50W Max. fixture lumen output: 7300lm, efficacy: 146lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation Multipower driver module with 8 power settings meet all installation needs with one single product, selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class III. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.1464mmx37.4mmx37mm

Technische activa

Afmetingen (mm)



Fotometrie



PIXO LINE 1500 UGR19 830 BLACK

Artikelnummer 0007827



Physical data

Kleur behuizing	Zwart
IP waarde	IP20
IK waarde	IK03
Lengte (mm)	1464
Breedte (mm)	37
Hoogte (mm)	37.4
Gewicht (kg)	0.9

Packaging

EAN code	5410288078274
Enkele lengte verpakking (cm)	147.0
Enkele breedte verpakking (cm)	4.3
Hoogte eenheidsverpakking (cm)	4.3
DUN14 (inner)	15410288078271
Eenheden per omdoos	10
Lengte omdoos (cm)	149.0
Breedte omdoos (cm)	24.0
Diepte omdoos (cm)	11.0

Safety data

Gloeidraad test (°)	650
Optimale bedrijfsomstandigheden (°C)	-20-40