

name	NOBEL PI TRACK 48V		
418302	NOBEL PI TRACK 48V mainscord black	TEXTURED BLACK	2700K
418316	NOBEL PI TRACK 48V mainscord black	TEXTURED BLACK	3000K
418334	NOBEL PI TRACK 48V mainscord white	TEXTURED WHITE	2700K
418308	NOBEL PI TRACK 48V mainscord white	TEXTURED WHITE	3000K
418396	NOBEL PI TRACK 48V mainscord black	BLACK + GOLD	2700K
418386	NOBEL PI TRACK 48V mainscord black	BLACK + GOLD	3000K
418394	NOBEL PI TRACK 48V mainscord black	TEXTURED WHITE + TEXTURED BLACK FOCUS	2700K
418387	NOBEL PI TRACK 48V mainscord black	TEXTURED WHITE + TEXTURED BLACK FOCUS	3000K
418301	NOBEL PI TRACK 48V mainscord black DALI	TEXTURED BLACK	2700K
418315	NOBEL PI TRACK 48V mainscord black DALI	TEXTURED BLACK	3000K
418333	NOBEL PI TRACK 48V mainscord white DALI	TEXTURED WHITE	2700K
418307	NOBEL PI TRACK 48V mainscord white DALI	TEXTURED WHITE	3000K
418395	NOBEL PI TRACK 48V mainscord black DALI	BLACK + GOLD	2700K
418385	NOBEL PI TRACK 48V mainscord black DALI	BLACK + GOLD	3000K
418393	NOBEL PI TRACK 48V mainscord black DALI	TEXTURED WHITE + TEXTURED BLACK FOCUS	2700K
418485	NOBEL PI TRACK 48V mainscord black DALI	TEXTURED WHITE + TEXTURED BLACK FOCUS	3000K

4.8V

166

Max.1700

314

30

safe distance to object	- 0,1m -
lamp / (lum.flux) / (colortemp)	Luxeon M 400lm (2700K) /429lm (3000K)
fitting	None
power	3,82W
voltage	48V DC
symbol	
gear	Converter incorporated
ip/class	IP20
application	Ceiling mounted
light distribution	Directional
dimmability	Not dimm or DALI dimmable
weight	0.7
beamangle	36°
CRI	80 (2700K) / 90 (3000K)
SDCM	3

