

name	HEKOWA SINGLE BEAM IP65 350mA		
ref	473226 HEKOWA SINGLE BEAM SPOT 2700K 350mA TEXT BLACK 473223 HEKOWA SINGLE BEAM SPOT 2700K 350mA SILVER ANTHRACITE 473229 HEKOWA SINGLE BEAM SPOT 2700K 350mA SILVER SAND 473203 HEKOWA SINGLE BEAM SPOT 2700K 350mA TEXTURED GREY 473626 HEKOWA SINGLE BEAM PUCK 2700K 350mA TEXT BLACK 473623 HEKOWA SINGLE BEAM PUCK 2700K 350mA SILVER ANTHRACITE 473629 HEKOWA SINGLE BEAM PUCK 2700K 350mA SILVER SAND 473603 HEKOWA SINGLE BEAM PUCK 2700K 350mA TEXTURED GREY 473726 HEKOWA SINGLE BEAM BEACON 2700K 350mA TEXT BLACK 473723 HEKOWA SINGLE BEAM BEACON 2700K 350mA SILVER ANTHRACITE 473729 HEKOWA SINGLE BEAM BEACON 2700K 350mA SILVER SAND 473703 HEKOWA SINGLE BEAM BEACON 2700K 350mA TEXTURED GREY		
	473236 HEKOWA SINGLE BEAM SPOT 3000K 350mA TEXT BLACK 473233 HEKOWA SINGLE BEAM SPOT 3000K 350mA SILVER ANTHRACITE 473239 HEKOWA SINGLE BEAM SPOT 3000K 350mA SILVER SAND 473213 HEKOWA SINGLE BEAM SPOT 3000K 350mA TEXTURED GREY 473636 HEKOWA SINGLE BEAM PUCK 3000K 350mA TEXT BLACK 473633 HEKOWA SINGLE BEAM PUCK 3000K 350mA SILVER ANTHRACITE 473639 HEKOWA SINGLE BEAM PUCK 3000K 350mA SILVER SAND 473613 HEKOWA SINGLE BEAM PUCK 3000K 350mA TEXTURED GREY 473736 HEKOWA SINGLE BEAM BEACON 3000K 350mA TEXT BLACK 473733 HEKOWA SINGLE BEAM BEACON 3000K 350mA SILVER ANTHRACITE 473739 HEKOWA SINGLE BEAM BEACON 3000K 350mA SILVER SAND 473713 HEKOWA SINGLE BEAM BEACON 3000K 350mA TEXTURED GREY		
	<div><div><div><div><div><div></div><div>108</div><div>78</div><div>30</div><div>60</div><div>60</div></div><div>SPOT</div></div><div><div><div><div><div><div></div><div>30</div><div>78</div><div>60</div><div>108</div><div>60</div></div><div>PUCK</div></div><div><div><div><div><div><div></div><div>30</div><div>156</div><div>60</div><div>108</div><div>60</div></div><div>BEACON</div></div></div></div></div></div></div></div></div></div></div>		
safe distance to object	<div><div><div></div></div> - 0,1m - <div><div></div></div></div>		
lamp / (lum.flux) / (colortemp)	LUXEON M	400lm/429lm	2700K / 3000K
fitting	NONE		
watt / (Vf)	3.82W	Vf=10,95V	
voltage or current	350 mA DC		
symbol	<div><div><div></div></div></div>		
gear	Converter not included		
ip/class	IP65	<div><div></div></div>	
application	Exterior - Interior		
orientability	Wall mounted		
dimmability	PWM dimmable		
weight	<div><div><div>0.8</div></div></div>		
beamangle	36°		
CRI	90		
SDCM	3		

