


G4, GZ4, G5.3, GX5.3, G6.35, GY6.35 Lampholders, Accessories

For low-voltage halogen incandescent lamps


The lampholders listed in this chapter permit the use of lamps with different bases. It is important to ensure that under no circumstances a lamp

with a smaller pin diameter is used if a lamp with a larger pin diameter has already been used.


G/GZ4, G/GX5.3, G/GY6.35 lampholder
 Casing: LCP, natural, T270
 Nominal rating: 8/24 (for G4/GZ4 lamps: 4/24)
 Multipoint contacts: CuNiZn
 Push-in terminals for stranded conductors with ferrule on bare end of core \varnothing 1.4–1.8 mm
 Fixing holes for screws M3
 Weight: 2.4 g, unit: 1000 pcs.
 Type: 33300
Ref. No.: 109547



Cover caps
 For push-fit onto lampholders type 333
 External thread 20.8x2
 Material: LCP, natural
 Moulded thread: M10x1
 Weight: 3.8 g, unit: 1000 pcs.
 Type: 97255
Ref. No.: 109548



Screw rings
 For components with external thread 20.8x2
 Weight: 1.7/1.4 g, unit: 1000 pcs.
 Type: 97257
Ref. No.: 109550 PPS, black
Ref. No.: 507490 LCP, natural



G/GZ4, G/GX5.3, G/GY6.35 lampholder
 Casing: LCP, natural, T270
 Nominal rating: 8/24 (for G4/GZ4 lamps: 4/24)
 Multipoint contacts: CuNiZn
 Push-in terminals for stranded conductors with ferrule on bare end of core \varnothing 1.4–1.8 mm
 Fixing holes for screws M3
 Weight: 2.6 g, unit: 1000 pcs.
 Type: 33400
Ref. No.: 109674

